



QSW-IM1200-8C (Legacy)

| | |
|-------------------------------|--|
| Management Type | Web Managed |
| Number of Ports | 12 |
| 10GbE SFP+ | 4 |
| 10GbE SFP+/RJ45 Combo Ports | 8 |
| Management Port | 1 x 1GbE RJ45 |
| Power Supply Description | Adapter |
| Max. Power Consumption | 78W |
| Input Power Type | DC |
| Input Voltage Range | 9V-54V |
| MAC Address Table | 32K |
| Total Non-Blocking Throughput | 120Gbps |
| Switching Capacity | 240Gbps |
| Management Interface | Web |
| Console | RS232 |
| Fanless | Yes |
| Supported Standards | IEEE 802.3 Ethernet IEEE 802.3u 100BASE-T IEEE 802.3ab 1000BASE-T IEEE 802.3bz 2.5G/5GBase-T IEEE 802.3an 10G BASE-T IEEE 802.3z 1000BASE-SX/LX IEEE 802.3ae 10G Fiber IEEE 802.3x Full-Duplex Flow Control IEEE 802.1Q VLAN Tagging IEEE 802.1w RSTP IEEE 802.3ad LACP IEEE 802.1AB LLDP (IEEE 802.1p Class of Service) |

| | |
|----------------------------|---|
| Form Factor | Rackmount |
| LED Indicators | Per Port: Speed/Link/Activity Per System: Status/Power1/Power2/Power3 |
| Buttons | Reset button |
| Dimensions (HxWxD) | 43.5 x 285 x 238 mm |
| Weight (Net) | 4.58 kg |
| Weight (Gross) | 5.31 kg |
| Operating Temperature | Natural convection (in airy environments 0.5~0.7m/s) operating temperature -30°C-65°C (-22°F -149°F) in airy environments Non natural convection operating temperature -30°C-45°C (-22°F -113°F) |
| Relative Humidity | 5~95% Non-condensing |
| Certifications | CE, FCC, VCCI, BSMI |
| Electromagnetic Compliance | Class A |
| Jumbo Frames | 9K |
| Warranty | 2 Years |

Note: QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.